tel.: 61 . 830 29 04 tel.: 517 732 682





V60, 2014

## **Maintenance service**



Program point:	year:	1	2	3	4	5	6	7	8	9	10	11	12	13
	km x 1000:	30	60	90	120	150	180	210	240	270	300	330	360	390
	miles x 1000:	18	36	54	72	90	108	126	144	162	180	198	216	234
Automatic														
transmission														
control - check the park /		x	х	x	×	×	×	x	×	×	×	x	×	×
neutral position														
(PNP) switch														
Parking brake					1					1				
- check and adjust		X	Х	X	×	×	×	X	×	×	×	X	X	X
External lighting														
- check the function		X	X	X	×	X	×	×	×	×	×	×	X	Х
Horn														
- check the signal		X	Х	X	Х	X	X	X	X	Х	X	X	Х	Х
Headlamp/fog														
lamp		×	×	×	x	x	×	x	×	x	×	x	x	x
- check and align		^	^	^	^	^	^	^	^	^	^	^	^	^
headlamps														
Washers and														
wipers for														
windshields and														
headlamps		X	Х	×	Х	X	X	X	X	Х	X	X	Х	Х
- check the function and for signs of														
wear														
Seat belts										1				
- check the function														
and for signs of		X	Х	X	X	X	X	X	×	X	×	X	X	X
wear														
Vehicle with														
camera for														
collision warning														
- clean the inside of		x	х	x	x	×	×	x	×	x	×	x	x	x
the windscreen in														
front of the camera														
lens														
Vehicles with	Calibration													
alcolock	must be													
- calibrate	performed													
	once a year,													
	when the													
	information													
	text in the													
	display indicates													
	this.													
Air filter,	5.1101													
passenger														
compartment		X	Х	X	×	×	×	X	X	×	X	X	X	Х
- replace														
Program point:	year:	1	2	3	4	5	6	7	8	9	10	11	12	13
	km x 1000:	30	60	90	120	150	180	210	240	270	300	330	360	390
	miles x	18	36	54	72	90	108	126	144	162	180	198	216	234
Daine the control	1000:													
Raise the vehicle	<u> </u>	1	1	1										
Engine,	In event of													
transmission, transmission	leakage from													
- check for leaks	the	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х
CHECK IOI IEAKS	transmission,													
	check the oil				l									

1	level.		l	I	I		1	I		I	I	I		I
Engine oil,														
oil filter		x	x	x	x	x	×	x	x	x	×	×	x	x
- change oil and oil		^	^	^	^	^	^	^	^	^	^	^	^	^
filter														
	For vehicles													
	used as													
Automatic	taxis or													
transmission	primarily													
The oil does not	used for													
normally need changing.	towing		×		×		×		×		×		×	
The oil must be	trailers,		^		^		^		^		^		^	
changed if	change the													
instructed to do so	oil according													
in the display	to the													
	service													
	program.													
Wheels and tires														
- check for damage		x	x	x	х	х	x	х	x	x	x	х	х	x
and signs of wear.														
Tires excl. spare														
wheel - check and adjust		×	x	x	x	х	x	x	x	x	x	х	х	x
the air pressure														
Program point:	year:	1	2	3	4	5	6	7	8	9	10	11	12	13
	km x 1000:	30	60	90	120	150	180	210	240	270	300	330	360	390
	miles x	18	36	54	72	90	108	126	144	162	180	198	216	234
	1000:	10	30	J-	, _	30	100	120	177	102	100	130	210	234
Drive shafts														
- check the play - check rubber			х		×		×		×		×		×	
bellows														
Brake pads,														
brake discs	Brake pads,	x	x	x	X	х	×	x	x	x	×	×	х	x
- check	front, check													
Brake lines,														
fuel lines,														
fuel filter			X		Х		X		X		X		Х	
- check for leakage and damage														
Fuel filter	In markets			<u> </u>										
- replace	with													
	contaminated													
	fuel:													
	- replace at													
	10,000 -													
	20,000 km				, , , , , , , , , , , , , , , , , , ,				, , , , , , , , , , , , , , , , , , ,				.,	
	intervals		Х		Х		X		X		X		Х	
	Change													
	only													
	according													
	to													
į į	lym/milec	I												
į l	km/miles			1		1	1	I		I	I			
- drain off the	interval.													
- drain off the condensation		х		x		х		х		х		×		x
condensation		×		х		x		х		х		x		×
		х		х		х		х		х		x		x
condensation Front suspension, steering system - check for wear		x	x	x	X	×	x	x	x	×	x	x	×	х
condensation  Front suspension, steering system - check for wear according to:		х	×	x	x	х	x	х	x	х	x	х	x	х
condensation  Front suspension, steering system - check for wear according to: Wheel angles check		X	x	X	x	x	x	х	x	х	x	x	x	X
condensation  Front suspension, steering system - check for wear according to: Wheel angles check Rear wheel		x	x	X	×	×	x	х	x	x	x	×	×	X
condensation  Front suspension, steering system - check for wear according to: Wheel angles check Rear wheel suspension		x		x		х		×		×		x		X
condensation  Front suspension, steering system - check for wear according to: Wheel angles check  Rear wheel suspension - check for wear		x	x	x	x	х	x	X	x	X	x	x	x	X
condensation  Front suspension, steering system - check for wear according to: Wheel angles check Rear wheel suspension		x		x		x		x		x		x		x

ı														
bevel gear	the oil level if													
- check for leaks	there is		х		×		×		×		×		×	
	leakage													
AWD: Propeller														
shaft, pilot														
bearing,			×		×		×		l x		×		×	
universal joint			^				^		^					
- check for signs of														
wear														
Lower the vehicle	1		_	_							- 10		4.5	1 4 5
Program point:	year:	1	60	90	4 120	5	6	7	8	9	10	11 330	12	13
	km x 1000: miles x	30	60	90	120	150	180	210	240	270	300	330	360	390
	1000:	18	36	54	72	90	108	126	144	162	180	198	216	234
Air cleaner (ACL)	Clean the air													
engine (ACL)	cleaner (ACL)													
- replace	housing.													
	Change								,					
	only		X		X		X		X		X		X	
	according													
	to													
	km/miles													
Fluid lavels	interval.													
Fluid levels -														
engine compartment														
- check and adjust														
the brake fluid,														
clutch fluid,		X	Х	X	X	Х	X	X	X	X	X	X	X	X
power steering														
fluid,														
washer fluid.														
coolant														
Engine coolant														
- check and adjust														
the		X	X	X	×	X	×	×	×	×	×	×	×	×
antifreeze/corrosion														
protection rating  Vehicles with		-												
temporary tire														
sealing kit														
- check sealant														
container														
- replace every four														
years (see decal)														
Program point:	year:	1	2	3	4	5	6	7	8	9	10	11	12	13
	km x 1000:	30	60	90	120	150	180	210	240	270	300	330	360	390
	miles x	18	36	54	72	90	108	126	144	162	180	198	216	234
	1000:	ļ- <b>"</b>		ļ-	ļ <b>-</b>									
Outer accessory														
drive belt and mechanical belt														
tensioner														
- replace according	For engine													
to the service	No.: -884797		X				x			х			х	
program														
or:														
- replace at max.														
10 year intervals		L	<u> </u>	L									<u> </u>	
Outer accessory														
drive belt (with														
hydraulic belt														
tensioner)	From ongine													
-replace the belt	From engine No.: 884798-			V			V			v			v	
according to the	1046801			Х			X			Х			Х	
service program,	1040001													
or:	1	İ	1	Ì	l		Ī	Ì	1	I		ĺ	ĺ	
- replace the belt at														

year interval	1		l	l	l	I		I	I		1	l		
Hydraulic belt														
tensioner														
- replace according to the service	From engine													
program	No.: 884798-						Х						Х	
or:	1046801													
- replace at max.														
10 year intervals Outer accessory														
drive belt (with														
mechanical belt														
tensioner) -replace the belt	From engine													
according to the	No.:			×			x			х			х	
service program,	1046802-													
or: - replace the belt at														
a maximum 10														
year interval														
Mechanical belt														
tensioner - replace according														
to the service	From engine No.:													
program	No.: 1046802-						Х						Х	
or: - replace at max.	10.0002													
10 year intervals														
Inner auxiliary														
belt														
- replace according to the service														
program							Х						Х	
or:														
<ul><li>replace at max.</li><li>10 year intervals</li></ul>														
Timing belt,														
belt tensioner														
idler pulley - replace according														
to the service							x						х	
program														
or:														
<ul><li>replace at max.</li><li>10 year intervals</li></ul>														
Brake fluid	Recommend													
- replace	that a													
	customer with normal													
	mileage has		x		х		х		x		х		х	
	the fluid													
	replaced every other													
	year.													
	The oil must be													
	changed													
	every year													
	if the car is used for	х	х	x	х	х	х	х	x	х	х	x	х	х
	mountain													
	driving or is													
	mainly used in humid													
	climates.					<u></u>		L_						
SRI														
- set the service reminder indicator	Resetting the	х	х	х	x	x	x	x	x	x	x	x	х	х
(SRI) to zero	service													
1	reminder		l			l		l	l		l	l .		

indicator						
(SRI)						